

The KAIVAC 1250

EQUIPMENT SPECIFICATIONS

DESCRIPTION

Water Tank	45 Litres (12 Gallons)
Spray Time	16 Minutes
Restroom Fixtures/Tank	~45
Flow Rate	2.8 L/min
Pressure	34.5 bars (500 psi)
Vac Tank	30 Litres
See-Through Vac Tank	Yes
Dump Hose	66 cm Long
Toilet Dumping	Yes
Vac Tank Cleanout	100% @ 27 secs
Method of Dumping	Drain Hose
Vac Motor Lift	330 cm
Vac CFM	3172 L/min
HEPA Blow Feature	483 km/h
HEPA Filtered Exhaust	Yes - Replaceable

CHEMICAL

Moulded-In Chemical Holder	1 Gallon, 2 Quart
Chemical Switching	Single/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

ELECTRICAL

Volts (Universal)	100-240V; 50-60 Hz
Amps Total	14.5 amp
RCD	Yes

CORDS AND HOSES

Vac Hose	15 m Slinky
Spray Line	14 m
Quick-Connect Gun	Yes
Electrical Cord	7.5 m
Blow Hose	10 m Slinky

BODY

Rotational Mould	Yes
Removable Engine Compartment	Yes – Black Box Technology
Weight	42.4 kg
Size (H x L x W)	96.5 x 55.9 x 50.8 cm
Hard Rubber Tire	2 x 12.7 cm
Casters	2 x 10.2 cm Locking
Stair Climbing Wheels	Yes
Handle	Moulded-In
Parking Brake	Yes

TOOLS INCLUDED

Vac Wand Aluminium	2-Piece
Squeegee Head	35 cm
Blow Nozzle	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
Tote Bag	57 Litres

WARRANTY WITH KAIVAC CHEMICALS

Body	5 Years
Parts	3 Years
Labor	1 Year

