

The KAIVAC 2150

EQUIPMENT SPECIFICATIONS

• DESCRIPTION

Water Tank	80 Litres (21 Gallons)
Spray Time	21 Minutes
Restroom Fixtures/Tank	~ 80
Flow Rate	3.78 L/min
Pressure	34.5 bars (500 psi)
Vac Tank	72 Litres
See-Through Vac Tank	Yes
Dump Hose	107 cm Long
Toilet Dumping	Yes
Vac Tank Cleanout	100%
Method of Dumping	Drain Hose
Vac Motor Lift	330 cm
Vac CFM	3172 L/min
HEPA Blow Feature	483 km/h
HEPA Filtered Exhaust	Yes - Replaceable

• CHEMICAL

Moulded-In Chemical Holder	1 Gallon, 2 Quart
Chemical Switching	Dual/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

• ELECTRICAL

Volts (Universal)	100-240V; 50-60 Hz
Amps Total	14.5 amp
RCD	Yes

• CORDS AND HOSES

Vac Hose	23 m
Spray Line	23 m
Quick-Connect Gun	Yes
Electrical Cord	15 m
Blow Hose	10 m Slinky

• BODY

Rotational Mould	Yes
Weight	72.1 kg
Size (H x L x W)	129.5 x 81.3 x 61.0 cm
Flat-Free Non-Marking	2 x 25.4 cm
Pneumatic Tires	
Casters	2 x 12.7 cm Locking
Stair Climbing Wheels	Yes
Handle	Moulded-In
Tray	Moulded-In
Parking Brake	Yes

• TOOLS INCLUDED

Vac Wand Aluminium	2-Piece
Squeegee Head	35 cm
Blow Nozzle	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
Tote Bag	57 Litres

• WARRANTY

With Kaivac Chemical Usage	24 Months
With Other Chemical Usage	12 Months

