

The KAIVAC 1750

EQUIPMENT SPECIFICATIONS

DESCRIPTION

Water Tank	65 Litres (17 Gallons)
Spray Time	17 Minutes
Restroom Fixtures/Tank	~ 65
Flow Rate	3.8 L/min
Pressure	34.5 bars (500 psi)
Vac Tank	65 Litres
See-Through Vac Tank	Yes
Dump Hose	66 cm Long
Toilet Dumping	Yes
Vac Tank Cleanout	100%
Method of Dumping	Dump Hose
Vac Motor Lift	330 cm
Vac CFM	3172 L/min
HEPA Blow Feature	483 km/h
HEPA Filtered Exhaust	Yes – Replaceable
Decibels (dB)	69 dB

CHEMICAL

Moulded-In Chemical Holder	3 Gallon, 1 Quart
Chemical Switching	Dual/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

ELECTRICAL

Volts (Universal)	100-240V; 50-60 Hz
Amps Total	14.5 amp
RCD	Yes

CORDS AND HOSES

Vac Hose	14 m
Spray Line	14 m
Quick-Connect Gun	Yes
Electrical Cord	15 m
Blow Hose	10 m Slinky

BODY

Rotational Mould	Yes
Removable Engine Compartment	Yes – Black Box Technology
Weight	55.8 kg
Size (H x L x W)	102 x 81 x 56 cm
Flat-Free Non-Marking Pneumatic Tyres	2 x 20.3 cm
Casters	2 x 12.7 cm Locking
Handle	Moulded-In
Tray	Moulded-In
Parking Brake	Yes

TOOLS INCLUDED

Vac Wand Aluminium	Yes
Squeegee Head	35 cm
Blow Nozzle	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
Tote Bag	57 Litres

WARRANTY WITH KAIVAC CHEMICALS

KaiTutor Onboard Training System	Compatible
Gatling Tool Range	Compatible
Carpet Extraction Tool	Compatible
Upholstery Tool	Compatible
Grout Turbo Tool	Compatible
Trash Compactor	Compatible
Wide Area Squeegee Head	Compatible
Stair Climbing Wheels	N/A

